

C € 0085



CERT

EC type examination certificate
EG-Baumusterprüfbescheinigung

CE-0085BS0269

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Pressure Equipment Directive (2014/68/EU) <i>EG-Druckgeräterichtlinie (2014/68/EU)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Düker GmbH Hauptstraße 39-41, D-63846 Laufach
Distributor <i>Vertreiber</i>	Düker GmbH Hauptstraße 39-41, D-63846 Laufach
Product Category <i>Produktart</i>	gas fittings: Shut-off valve for local gas distribution <= PN 16 (4313)
Product Description <i>Produktbezeichnung</i>	shut-off slide valve with thread connections or with integrated transition joints to pipes made of PE-HD
Model <i>Modell</i>	1004
Test Reports <i>Prüfberichte</i>	laboratory control test: 17/0176/4313/083 from 30.06.2017 (EBI)
Test Basis <i>Prüfgrundlagen</i>	2014/68/EU A III B Baumusterprüfung (15.04.2014)

7/0228-04-A-DE

Date of Expiry / File No. 18.07.2027 / 17-0208-GDV
Ablaufdatum / Aktenzeichen

06.02.2018 Kö A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of pressure equipment under EC Directive

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Druckgeräten und Baugruppen gemäß Richtlinie



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-02

DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases according to G260	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
1004	nominal diameter: DN 25 max. allowable pressure PS: 16 bar	
1004	nominal diameter: DN 32 max. allowable pressure PS: 16 bar	
1004	nominal diameter: DN 40 max. allowable pressure PS: 16 bar	
1004	nominal diameter: DN 50 max. allowable pressure PS: 16 bar	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
1004	connection: on both sides internal thread Rp 1 to Rp 2 according to DIN EN 10226-1, max. permissible pressure PS = 16 bar.
1004	connection: integrated material connection connectors on both sides, with supports made of PE 100 (d 25 to 63), max. permissible pressure PS = 10 bar

Hints of Utilization / Remarks <i>Verwendungshinweise / Bemerkungen</i>
Body material: ductile cast iron EN-GJS-500-7 acc. DIN EN 1563 corrosion protection: powder coating ambient temperature range: -20 °C up to +60 °C operation: handwheel or ground installation kit The product is also marketed under the name 1004 by the company Schmieding Armaturen, Gottlieb-Daimler-Strasse 17, D-59439 Holzwickede.

DVGW